

Bronze Globe Valve (Screwed)

Article No. 1033

Salient Features

Suitable For





- Screwed Female Ends to IS 554 / BS 21 / ISO 7.
- Screwed in Bonnet, Rising Stem.
- Provision for re-packing under pressure.
- High Quality PTFE Gland Packing.
- Design Standard IS 778, Class-1.
- Provided with unbreakable sheet metal handwheel for convenient operation.

Also available with Open-Shut Indicator and Locking Device and with PTFE Seating, at a nominal extra price.

Steam

Water

Oil

Air

Gases


Test Pressure (Hydraulic) Shell: 1.5 MPa Seat: 1.0 MPa

Materials of Construction

Name of Part	Material Specification		
Body & Bonnet	Bronze IS 318 Gr. LTB 2		
Disc & Disc Nut	Bronze IS 318 Gr. LTB 2		
Stem	Forged Brass IS 6912 Gr. FLB		
Gland Nut & Gland	Bronze / Forged Brass IS 318 Gr. LTB 2 / IS 6912 Gr. FLB		
Handwheel	Cast Iron / Sheet Metal IS 210 Gr. FG 200 / IS 4030		
Screw / Bolt & Washer	Carbon Steel	Carbon Steel IS 1367	
Gland Packing	PTFE	BS EN 12086-1	

Sizes / Dimensions

Inches	mm	Α	В	С
1/4	8	47	67	50
3/8	10	50	70	50
1/2	15	60	90	55
3/4	20	70	105	60
1	25	80	115	70
1 1/4	32	95	127	80
1 1/2	40	110	138	90
2	50	125	162	100
2 1/2	65	160	183	115
3	80	180	207	125
4	100	216	250	160



Phones: +91 181 4676666 (100 Lines)
Facsimile: +91 181 2792500 & 2251600
Email: zoloto@vsnl.com & sales@zolotovalves.com
Web: http://www.zolotovalves.com