

## Bronze Sleeve Packed Water Level Gauge (Screwed)

Article No. 1049



### Salient Features

- Screwed Male End to BSP.
- Automatic Shut Off Device in Water Arm.
- Available for both, Right Hand and Left Hand.
- High Quality Sleeve, Reinforced by metallic eye holes provided to avoid any clogging of passage.
- Each piece is fitted with self adjusting inverted taper plug (Stainless Steel) which forms a seal in the renewable moulded asbestos sleeve.
- Sleeve can easily be positioned by a rib which fits in the corresponding groove of the body.

Glass Tube is not provided with this product.

### Suitable For

Steam	■
Water	■
Oil	
Air	
Gases	

Test Pressure (Hydraulic) 35.15 kg/cm<sup>2</sup>g (500 psig) Working Pressure (Steam) 17.58 kg/cm<sup>2</sup>g (250 psig)

Maximum Working Temperature 225°C

### Materials of Construction

Name of Part	Material	Specification
Arms & Plug	Bronze	IBR 282 (a) (iv) Gr.B
Bonnet & Handle	Bronze	IBR 282 (a) (iv) Gr.B
Drain Valve	Bronze	IBR 282 (a) (iv) Gr.B
Nipple & Union Nut	Bronze	IBR 282 (a) (iv) Gr.B
Stem & Ball	Stainless Steel	AISI 410 & AISI 304
Sleeve	Moulded Asbestos	-
Cone	Synthetic Rubber	IS 5192-1
Nut	Carbon Steel	IS 1367
Name Plate	Brass / Aluminium	IS 410 / BS EN 10154
Glass Tube	Toughened Glass	BS 3463

### Sizes / Dimensions

Inches	mm	A
1/2	15	118
3/4	20	118

