

Cast Steel Sleeve Packed Water Level Gauge (Flanged)

Article No. 1091



**Salient Features**

- Flanged End to BS 10 Table 'J'.
- Automatic Shut Off Device in Water Arm.
- Available for both, Right Hand and Left Hand.
- High Quality Sleeve, Reinforced by metallic eye holes, is provided to avoid any clogging of passage.
- Each piece is fitted with self adjusting inverted taper plug (Stainless Steel) which forms a seal in the renewable moulded asbestos sleeve.
- Sleeve can easily be positioned by a rib which fits in the corresponding groove of the body.

Glass Tube is not provided with this product.

**Suitable For**

Steam ■
Water ■
Oil
Air
Gases

Test Pressure (Hydraulic) Shell : 48 kg/cm<sup>2</sup>g (700 psig) Test Pressure (Steam) Seat : 24.50 kg/cm<sup>2</sup>g (350 psig)

Maximum Working Temperature 425°C

**Materials of Construction**

Name of Part	Material	Specification
Upper & Lower Arms	Cast Steel	IBR 73-80 Gr.B
Bonnet & Plug	Stainless Steel	AISI 410
Drain Valve & Handle	Cast Steel	IBR 73-80 Gr.B
Nipple & Union Nut	Stainless Steel	AISI 410
Stem & Ball	Stainless Steel	AISI 410 / AISI 304
Sleeve	Moulded Asbestos	-
Cone	Synthetic Rubber	IS 5192-1
Nut	Carbon Steel	IS 1367
Name Plate	Brass / Aluminium	IS 410 / BS EN 10154
Glass Tube	Toughened Glass	BS 3463

**Sizes / Dimensions**

Inches	mm	A
1/2	15	84
3/4	20	99

